

ENDLESS CHEVRON AND DIAGONAL FELT BELTS



Sandbelts are used in Wide Belt Sanding Machines such as Costa, SCM, DMC, Timesavers and other brands. Used underneath the abrasive belt, the segmented pressure pads act as a cushion, reducing chatter and buffeting effects. With the added benefit of reducing heat generated by friction and pressure of the abrasive pads.

For special applications, other types of material, patterns, and backings are available.

Benefits:

- Reduces heat
- Support belt for use in cross sanding operations or narrow sanding belts
- High tensile strength and durability
- For high quality sanding requirements

Data Sheet

Tensile Core Member	EFF. Pull at 1% Elongation	Material	Approx. Thickness
Fabric	3,5	Polyester	1

Top Cover	Thickness mm	Density g/cm ²	Color
Felt	4	0,42	White

Type	Belth Width mm	Felt With mm	Felt Pitch mm
Chevron	140, 150	20	10, 15, 20, 30, 40
Chevron	200	20	20
Diagonal	90, 100, 140, 150	10, 20	10, 20
Diagonal	1330, 1360, 1380, 1430, 1630	10	10
Diagonal	1120, 1350, 1360, 1370, 1400, 1420, 1450, 1650, 1660, 1680, 1970	15	8
Diagonal	1650, 1660	10	8
Diagonal	1970, 2210	15	10